

How to Specify Treefrog Veneer

Wood Veneer Laminate must be Treefrog.

t r e e f r o g[®]

sales@treefrogveneer.com

800 807-7341

treefrogveneer.com

Treefrog #:

Treefrog Name:

Size:

Rep/Distributor:

How to Buy Treefrog.

Treefrog is based in Easthampton, MA and is sold through our national distributor network. It is likely you are already familiar with our distributor in your area, they sell many building supplies and materials.

To find the distributor nearest you, please call or email.

Notes:

TREEFROG TECHNICAL DATA

Below please find an abbreviated version of our technical data. More complete info is viewable/downloadable at treefrogveneer.com.

USE:

Treefrog is recommended for interior use on vertical and light-duty horizontal surfaces. Please contact Treefrog if you are uncertain about the use of Treefrog in any application. Caution should be taken on surfaces that may be exposed to harsh chemicals, acidic beverages (alcoholic, colas, etc.) without cleaning the surface for lengthy periods of time.

STORAGE:

Store flat, not on edge. The laminates should be stored face-up in a cool, dry area and in a completely supported flat position. Use a top sheet of chipboard or similar material to hold stored sheets flat. Protect material from twist, rack and edge damage.

SUBSTRATES AND BALANCING SHEETS:

Treefrog must be laminated to MDF, HDF, better quality particle-board and very good quality plywood (Baltic Birch, for example). Do not apply directly to gypsum board (sheet rock), concrete or poor quality particle board. Balancing sheets of similar thickness and material are recommended for balanced construction to prevent warping.

TREEFROG TECHNICAL DATA *CONT.*

PROTECTIVE MASK:

Although Treefrog is supplied with a protective mask, care should be taken when handling. Exposure of masked sheets to light or heat for long periods of time may cause problems with the removal of the protective mask. It is recommended to leave this mask on the surface of the laminates during processing work. Additionally, masking tape, for extra protection in routing work, may be applied over the protective mask. Color uniformity and other quality checks should be carried out on the sheets beforehand by lifting up the edge of the mask and laying it back down.

CLEANING AND MAINTENANCE:

Clean with a soft cloth using mild soap and water or nonabrasive glass and metal cleaning liquids. Do not use ammonia, abrasive cleaners or pads, or harsh solvents.

SHIPPING:

Treefrog may be rolled for shipping, with limitations. 4' x 8' sheets may be rolled 5 to a carton, except Treefrog Press (Plank, Carved, Rough Cut designs) which can only ship 2 to a carton rolled. Treefrog Groove, and any 4' x 10' Treefrog sheets can be rolled 2 to a carton. We recommend flat packs and skidded crates for larger quantities.

t r e e f r o g[®]